

BRENNABOR T-46E



The belt drive on the e-trekker is quiet, low-maintenance and durable, which is why it fits so well into the overall concept of the comfortable day-to-day e-bike.



ZUSÄTZLICHE INFORMATIONEN

Frame	Frame	Semi-Integrated-Bosch-Frame, Aluminium 6061
	Frame shape	Deep Herren
	Frame height	45 cm 50 cm 52 cm 55 cm 56 cm 60 cm
	Frame shape/height	Deep/45 cm Deep/50 cm Deep/55 cm Herren/52 cm Herren/56 cm Herren/60 cm
	Colours	
	Fork	
Drive system	Drive system	Bosch
	Motorposition	Mittelmotor
	Motor	BOSCH Mittelmotor Gen.3 "Active Line PLUS", 36 V, 250 W
	Energy content	
	Battery capacity	
	Display	
	Battery charger	BOSCH 2 Ah
Cockpit	Sensor	Tretkraftmessung im Motor + Geschwindigkeitssensor
	Support up to	25 km/h
	Handlebars	SATORI "Wien", 680 mm, Ø 31,8 mm
	Handlebar grips	CONTEC "Tour Wing"
	Stem	Alu, verstellbar, Ø 31,8 mm
	Saddle	SELLE ROYAL "Vivo Ergo"
	Seat Post	SATORI "Harmony LT2", gefedert, Ø 30,4 mm, Alu

Brake	Brake	
	Brake lever	
	Rear-wheel brake disc	
	Front-wheel brake disc	
Wheels	Wheel rims	
	Rear-wheel hub	SHIMANO "Nexus" 8-Gg. LL, CL
	Front-wheel hub	SHIMANO "HB-TX505", QR, CL
	Tyres	CONTINENTAL "Contact Plus", 47-622, Reflex
	Tire size	28 Zoll/inch
Lights	Spokes	Niro, black
	Front light	CONTEC "Dlux 50 E+", 50 Lux
	Rear light	CONTEC "CTL-335 E"
Shifting system	Shifting system	Nabenschaltung
	Gears	
	Shifting	8-Gang SHIMANO "Nexus" LL
	Gear shift	SHIMANO "SL-S503", 8-Gg.
	Bottom bracket	BOSCH
	Cassette	
	Chain / Belt	
	Sprocket	GATES "CDX, 46 Z.
	Crank	FSA "CK220", 170mm

Extras

Mudguards

[SKS, Kunststoff](#)

Rack

Chainguard

[HESLING "Velo" Bosch Gen.3](#)

Locks

[ABUS 4750](#)

Kick stand

[URSUS "Wave" verstellbar](#)

Pedals

[MARWI "SP-822"](#)